

## 500 KG PP JUMBO BAGS FOR AAC

500 KGS POLYPROPYLENE JUMBO-  
BAGS WITH DOUBLE PVC LINER  
(CAP;- 500KGS)

WITH DOUBLE SPOUT.  
MATERIAL TO BE FILLED ANHY.  
AL.

CHLORIDE

1 DESCRIPTION OF THE PACKAGE;  
WOVEN POLY PROPYLENE (10X10)  
MESH, FLEXIBLE BULK CONTAINER

2 DIMENSION OF THE BAG SHAPE  
RECTANGULAR, BOX TYPE

WITH FILLING & DISCHARGE  
SPROUT (DOUBLE SPROUT)

A- MIN. LENGTH OF THE JUMBO  
BAG

610 MM

B- MIN. WIDTH OF THE JUMBO BAG

610 MM

C- MIN. HIEGHT OF THE JUMBO  
BAG

1000 MM

3 : SAFE WORKING LOAD 500KGS.

4: STRAP(LIFTING LOOP) 4 NOS.

240 MM(L) X 60 MM (W)

A-DOUBLE STICED IN SANDWICH  
PATTREN WITH WITH CORNER STICH

B- LIFTING LOOP EXTENDED IN  
FULL HIGHT OF BAGS

FOR EXTRA STRENGTH

5 STITCHING;- DOUBLE STICH

WITH PP THREAD

6 POSITION OF GLUE TO

HOLD LINERS : 8 NOS.

7 PRINTING :- TWO SIDE

PRINTING

IN BLUE COLOUR

8 PRINTING MATTER

AS PER MATTER APPROVED BY GACL

9 WEIGHT OF THE COMPOSITE

BAG MIN : 3 KGS.

10 PVC LINER DOUBLE:-

600 GAUGE FOR JUMBO BAG

11 COLOUR OF THE BAG/FABRIC

;- WHITE

DRAWING NO.

AS PER SPECIFICATION