

HM-HDPE CARBUOYS - 50 LITRES CAPACITY FOR H2O2 - BARODA

OXFORD BLUE COLOUR HM-HDPE
NON-ROLLING ROCKET TYPE
CARBUOYS OF 50 LITRES CAPACITY
MATERIAL TO BE FILLED : 50 KGS
HYDROGEN PEROXIDE (35% TO 70%)
TYPE OF CARBUOYS REQUIRED:-
NON ROLLOING ROCKET TYPE
HM-HDPE CARBUOYS.
NO.OF OPENINGS : 1 NO.OPENING
WITH BREATHER CAP WITH FILTER
PAD & MUSHROOM CAP.
(GORE VENT REQUIRED).
MOUTH OPENING:- 45 MM +/- 1 MM
NO.OF HANDLES : TWO AT SIDES.
INSIDE REQUIREMENT : THROUGHL
CLEANED FROM INSIDE & SHOULD
HAVE SMOOTH SURFACE.
ZERO LEAK SEALING ARRANGEMENT
TO BE PROVIDED
BREATHER CAP COLOUR : YELLOW
CAP SEALING : ALL CAPS ARE
REQUIRED WITH SEALING ARRANGE-
MENT. SEAL SHOULD BE DETACHAB-
LE TYPE AND IS REQUIRED TO BE
FIXED ONLY ON FINAL TIGHTENING
OF CAP ON CARBUOYS.SEAL SHOULD
BEAR GACL NAME.
DIMENSION OF CARBOYS
L X B X H (MM) 410 X330 X570 +/- 5 MM
EMPOSSING REQUIREMENT :-

-
1. ON CARBUOYS :-
MONTH & YEAR OF MANUFACTURE
LOGO & NAME OF MANUFACTURE
LOGO & NAME OF GACL
SPACE FOR UN NUMBER.
 2. ON CAPS :-
MONTH & YEAR OF MANUFACTURE
GACL LOGO,
LABEL CLASS : 5.1
SUBSIDIARY RISK LABEL OF
CLASS : 8
UN NUMBER : PAGE : 5151
ADMT : 27-97
I.S.STANDARD : IS 6312
WEIGHT OF CARBUOY:2.4 KG.+/-2%
WATER CAPACITY : 50 LITRES.
STANDARD TEST REQUIRED AS PER
I.S. & UN NO.
- APPEARANCE
- DROP TEST
- HYDRAULIC TEST
- LEAKAGE TEST
- STOCK LOAD TEST